



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H31 VALUE

PRESSURE

130 ÷ 170
bar

FLOW RATE

500 ÷ 800
l/h

ABSORBED POWER

2,5 ÷ 4,7
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ IPC TEMPERATURE STABILIZER - ATC



PW-H31
VALUE

PW-H31/4
VALUE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



CIRCULAR
DESIGN
& OPERATION



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC
PUMP



IPC'S
EXCLUSIVE
BOILER

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS



USER FRIENDLY ACCESS TO
ADJUSTMENT.



STURDY AND LARGE TANK
AND ACCESSORIES STORAGE.

TECHNICAL DATA

3 WHEELS		PW-H31 D1309P M	PW-H31 D1310P4 M	PW-H31 D1509P4 M	PW-H31 D1708P4 M	PW-H31 D1713P T
Code		IDAC41351	IDAC41352	IDAC41353	IDAC41354	IDAC41355
4 WHEELS		PW-H31/4 D1309P M	PW-H31/4 D1310P4 M	PW-H31/4 D1509P4 M	PW-H31/4 D1708P4 M	PW-H31/4 D1713P T
Code		IDAC41356	IDAC41357	IDAC41358	IDAC41359	IDAC41360
PERFORMANCE						
Operating pressure	bar/Mpa	30-130/3-13	30-130/3-13	30-150/3-15	30-170/4-17	30-170/3-17
Flow rate	l/h	280-540	300-600	300-540	300-500	400-800
Outlet water temperature	°C	30-110	30-110	30-110	30-110	30-110
Power supply	Ph-V-Hz/A	1-230-50/11,5	1-230-50/11,5	1-230-50/11,5	1-230-50/11,5	3-400-50/9,1
Absorbed power	kW	2,5	2,7	2,7	2,7	4,7
Motor pole/rpm		2-2800	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	37,8	37,8	37,8	37,8	37,8
Fuel consumption	Kg/h	3,2	3,2	3,2	3,2	3,2
Fuel tank	l	18	18	18	18	18
Detergent tank	l	-	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	m	82x63x87	82x63x87	82x63x87	82x63x87	82x63x87
Weight	Kg	80	80	80	80	90

STANDARD EQUIPMENT

CODE: IPPR40031
HANDGRIP G4000
CERAMIC TECH



CODE: LCPR40037
EXTENSION P50 ZINC
PLATED



CODE: UGLN40000
H.P. NOZZLE 1/4 15034 -
(FOR 1309)



CODE: UGLN49986
H.P. NOZZLE 1/4 1504 -
(FOR 1310/1713)



CODE: UGLN49985
H.P. NOZZLE 1/4 1503 -
(FOR 1509)



CODE: UGLN75421
H.P. NOZZLE 1/4 15025 -
(FOR 1708)



CODE: TBAP40308
HIGH PRESSURE HOSE
10 m



OPTIONAL ACCESSORIES

CODE: LCPR29362
HYDROBRUSH LANCE



CODE: SPID24939
FIXED HYDROBRUSH LANCE



CODE: KTRI40303
HOSE REEL KIT



CODE: LCPR40040
FOAMER KIT 1 l



CODE: RCIN10810
HOSE COUPLING M22



CODE: KTRI29377
FEEDING KIT



CODE: TBAP23853
DRAIN KIT 10 m



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40103
EXTENSION P70 + TPR255
Ø 0,4 - (FOR 1713)



CODE: LCPR40104
EXTENSION P70 + TPR255
Ø 0,35 (FOR 1309)



CODE: LCPR24943
SANDBLASTER KIT Ø 1,3 mm
(FOR 1309/1509/1708)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 1310/1713)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCLC49492
LANCE FOR WASHING
FLOORS Ø 0,35



CODE: KTRI40306
MAINTENANCE KIT 500H
(FOR 1309)



CODE: KTRI40316
MAINTENANCE KIT 500H -
(FOR 1310)



CODE: KTRI40307
MAINTENANCE KIT 500H
(FOR 1713)

