



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H61 VALUE

PRESSURE

150÷200
bar

FLOW RATE

800÷1150
l/h

ABSORBED POWER

5÷6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ IPC TEMPERATURE STABILIZER - ATC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ MAINTENANCE CHECK LED - MCL



PW-H61
VALUE

PW-H61/4
VALUE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



DIAD
DIRECT INJECTION
DETERGENT AND
ANTI-SCALE



CIRCULAR
DESIGN
& OPERATION



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC'S
EXCLUSIVE
BOILER



IPC
PUMP

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS.



USER FRIENDLY ACCESS TO
ADJUSTMENT AND LIQUID
REFILLING



NEW AND MORE RESISTANT
PLASTIC.

TECHNICAL DATA

3 WHEELS		PW-H61 D1813P4 T	PW-H61 D1915P4 T	PW-H61 D1517P4 RT	PW-H61 D1719P4 T	PW-H61 D2017P4 T
Code		IDAC41361	IDAC41362	IDAC41377	IDAC41364	IDAC41363
4 WHEELS		PW-H61/4 D1813P4 T	PW-H61/4 D1915P4 T	PW-H61/4 D1517P4 RT	PW-H61/4 D1719P4 T	PW-H61/4 D2017P4 T
Code		IDAC41365	IDAC41366	IDAC41381	IDAC41368	IDAC41367
PERFORMANCE						
Operating pressure	bar/Mpa	30-180/3-18	30-190/3-19	30-150/3-19	30-170/3-17	30-200/3-20
Flow rate	l/h	450-800	450-900	500-1000	600-1150	500-1000
Outlet water temperature	°C	30-110	30-110	30-110	30-110	30-110
Power supply	Ph-V-Hz/A	3-400-50/9,7	3-400-50/10,6	3-400-50/10,6	3-400-50/13,2	3-400-50/13,2
Absorbed power	kW	5	5	5	6,4	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	70	70	70	≥70	≥70
Fuel consumption	kg/h	5,8	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	120	122	122	140	140

STANDARD EQUIPMENT

CODE: IPPR40025 HANDGRIP G6000	CODE: LCPR40087 EXTENSION P70 - INOX	CODE: UGLN49986 H.P. NOZZLE 1/4 1504 (FOR 1813)	CODE: UGLN05200 H.P. NOZZLE 1/4 1505 (FOR 1517)	CODE: UGLN49987 H.P. NOZZLE 1/4 15045 (FOR 1915/2017)
				
CODE: UGLN49994 H.P. NOZZLE 1/4 2506 (FOR 1719)	CODE: - ANTI-SCALE TREATMENT M421 1 Kg	CODE: TBAP40308 HIGH PRESSURE HOSE 10 m (FOR 1813/1915)	CODE: TBAP40309 HIGH PRESSURE HOSE 10 m (FOR 1517/1719/2017)	
				

OPTIONAL ACCESSORIES

CODE: SPID24939 FIXED HYDROBRUSH LANCE P70	CODE: LCLC41140 LANCE FOR WASHING FLOORS INOX	CODE: LCLC49492 LANCE FOR WASHING FLOORS Ø 0,35 (FOR 1915)	CODE: LCLC49494 LANCE FOR WASHING FLOORS Ø 0,55 (FOR 1719)	CODE: LCLC49493 LANCE FOR WASHING FLOORS Ø 0,45 (FOR 1813/1517/2017)
				
CODE: KTRI40235 HOSE REEL KIT	CODE: RCIN10810 HOSE COUPLING M22	CODE: TBAP23853 DRAIN KIT 10 m	CODE: LCPR40104 EXTENSIO P70 + TPR255 Ø 0,35 (FOR 1310/1813)	CODE: LCPR40135 EXTENSIO P70 + TPR255 Ø 0,45 (FOR 1517/1915/2017)
				
CODE: LCPR14859 SANDBLASTER KIT Ø 1,5 mm (FOR 1517/1915/2017)	CODE: LCPR14858 SANDBLASTER KIT Ø 1,4 mm (FOR 1813)	CODE: LCPR13557 SANDBLASTER KIT Ø 1,6 mm (FOR 1719)	CODE: PRCH40041 SAND BAG 25 Kg	CODE: PRCH40039 ANTI-SCALE TREATMENT M421 1 Kg X 6
				
CODE: PRCH40040 ANTI-SCALE TREATMENT M421 10 Kg	CODE: KTRI40314 MAINTENANCE KIT 500H (FOR 1813/1915)	CODE: KTRI40431 MAINTENANCE KIT 500H (FOR 2017)		
				



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H61 PREMIUM

PRESSURE

150÷200
bar

FLOW RATE

800÷1150
l/h

ABSORBED POWER

5÷6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ DIGITAL TEMPERATURE STABILIZER CONTROL - DTSC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ MAINTENANCE CHECK LED - MCL
- ▶ LED INDICATOR LIGHT REACHING TEMPERATURE - TL



PW-H61 PREMIUM

PW-H61/4 PREMIUM

MOST FREQUENTLY USE

AUTOMOTIVE

AGRICULTURE

CONSTRUCTION INDUSTRY

MUNICIPALITIES

DIY AND GARDENING

HEAVY INDUSTRY

INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



DIAD
DIRECT INJECTION
DETERGENT AND
ANTI-SCALE



CIRCULAR
DESIGN
& OPERATION



DIGITAL
DISPLAY
DD



IPC
PUMP



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC'S
EXCLUSIVE
BOILER

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS AND
DISPLAY



USER FRIENDLY ACCESS TO
ADJUSTMENT AND LIQUID
REFILLING



NEW AND MORE RESISTANT
PLASTIC.








TECHNICAL DATA

		PW-H61P D1813P4 T	PW-H61P/4 D1915P4 T	PW-H61P/4 D1517P4RT	PW-H61P D1719P4 T	PW-H61P D2017P4 T
3 WHEELS						
Code		IDAC41369	IDAC41370	IDAC41385	IDAC41372	IDAC41371
4 WHEELS						
Code		PW-H61/4PD1813P4T IDAC41373	PW-H61/4PD1915P4T IDAC41374	PW-H61/4PD1517P4RT IDAC41389	PW-H61/4PD1719P4T IDAC41376	PW-H61/4PD2017P4T IDAC41375
PERFORMANCE						
Operating pressure	bar/Mpa	30-180/3-18	30-190/3-19	30-150/3-19	30-170/3-17	30-200/3-20
Flow rate	l/h	450-800	450-900	500-1000	600-1150	500-1000
Outlet water temperature	°C	30-140	30-140	30-140	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/9,7	3-400-50/10,6	3-400-50/10,6	3-400-50/13,2	3-400-50/13,2
Absorbed power	kW	5	5	5	6,4	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	70	70	≥70	≥70	≥70
Fuel consumption	kg/h	5,8	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	120	122	122	140	140

STANDARD EQUIPMENT

CODE: IPPR40025 HANDGRIP G6000	CODE: LCPR40087 EXTENSION P70 - INOX	CODE: UGLN49986 H.P. NOZZLE 1/4 1504 (FOR 1813)	CODE: UGLN05200 H.P. NOZZLE 1/4 1505 (FOR 1517)	CODE: UGLN49987 H.P. NOZZLE 1/4 15045 (FOR 1915/2017)
				
CODE: UGLN49994 H.P. NOZZLE 1/4 UG.2506 (FOR 1719)	CODE: - ANTI-SCALE TREATMENT M421 1 Kg	CODE: TBAP40308 HIGH PRESSURE HOSE 10 m (FOR 1813/1915)	CODE: TBAP40309 HIGH PRESSURE HOSE 10 m (FOR 1517/1719/2017)	
				

OPTIONAL ACCESSORIES

CODE: SPID24939 FIXED HYDROBRUSH LANCE P70	CODE: LCLC41140 LANCE FOR WASHING FLOORS INOX	CODE: LCLC49492 LANCE FOR WASHING FLOORS Ø 0,35 (FOR 1915)	CODE: LCLC49494 LANCE FOR WASHING FLOORS Ø 0,55 (FOR 1719)	CODE: LCLC49493 LANCE FOR WASHING FLOORS Ø 0,45 (FOR 1813/1517/2017)
				
CODE: KTRI40235 HOSE REEL KIT	CODE: RCIN10810 HOSE COUPLING M22	CODE: TBAP23853 DRAIN KIT 10 m	CODE: LCPR40104 EXTENSIO P70 + TPR255 Ø0,35 (FOR 1813)	CODE: LCPR40135 EXTENSIO P70 + TPR255 Ø0,45 (FOR 1915/2017)
				
CODE: LCPR14859 SANDBLASTER KIT Ø 1,5 mm (FOR 1915/2017/1517)	CODE: LCPR14858 SANDBLASTER KIT Ø 1,4 mm (FOR 1813)	CODE: LCPR13557 SANDBLASTER KIT Ø 1,6 mm (FOR 1719)	CODE: PRCH40041 SAND BAG 25 Kg	CODE: PRCH40039 ANTI-SCALE TREATMENT M421 1 Kg X 6
				
CODE: PRCH40040 ANTI-SCALE TREATMENT M421 10 Kg	CODE: KTRI40314 MAINTENANCE KIT 500H (FOR 1813/1915)	CODE: KTRI40431 MAINTENANCE KIT 500H (FOR 2017)		
	